

Specification and Capacities for DAVIS Ultimate Duty Mixers

All Davis Ultimate Duty Mixers are furnished with our Paddle Agitator, Double Reduction Chain Drive, Complete V-Belt Drive, Motor Base and Cover with Hinged Section and Grate beneath. Limit Switch is attached to hinged section of cover. A full grate with limit switch can be furnished in place of cover. Mixer's tank is made of 1/4" plate. Drive is based on operation of mixer with 1750 RPM motor. If different RPM motor is used we must advised. Motor and starter not included. We will be pleased to quote upon request.

| Model | UD-2 | UD-3 | UD-5 | UD-10 | UD-20 | UD-30 | UD-40 | UD-60 |
|--|--------|--------|--------|--------|--------|--------|--------|--------|
| Mixing Capacity: | | | | | | | | |
| Cubic Feet | 12 | 18 | 30 | 60 | 90 | 115 | 150 | 180 |
| Cubic Yards | 2/5 | 2/3 | 1.1 | 2.2 | 3.3 | 4.2 | 5.5 | 6.7 |
| Cubic Meters | 0.34 | 0.51 | 0.85 | 1.7 | 2.55 | 3.25 | 4.24 | 5.09 |
| Gallons | 90 | 135 | 225 | 450 | 675 | 862 | 1125 | 1350 |
| Liters | 339 | 509 | 849 | 1699 | 2548 | 3256 | 4247 | 5096 |
| Mixing Capacity In Pounds Based On Ingredients Averaging: | | | | | | | | |
| 100# per cu. ft. | 1,200 | 1,800 | 3,000 | 6,000 | 9,000 | 11,500 | 15,000 | 18,000 |
| 90# per cu. ft. | 1,080 | 1,620 | 2,700 | 5,400 | 8,100 | 10,300 | 13,500 | 16,200 |
| 80# per cu. ft. | 960 | 1,440 | 2,400 | 4,800 | 7,200 | 9,200 | 12,000 | 14,400 |
| 75# per cu. ft. | 900 | 1,350 | 2,200 | 4,500 | 6,700 | 8,600 | 11,200 | 13,500 |
| 100 pounds per cubic foot represent the maximum bulk density that our Ultimate Duty Mixer is designed to | | | | | | | | |
| process. | | | | | | | | |
| H. P. Required | 10 | 10 | 15 | 30 | 40 | 50 | 75 | 100 |
| Tank Length | 2' 6" | 3' 9" | 5' 5" | 6' 8" | 7' 6" | 8' 4" | 9' 6" | 10' 0" |
| Tank Width | 2' 6" | 2' 6" | 2' 8" | 3' 5" | 4' 0" | 4' 3" | 4' 6" | 4' 10" |
| Tank Depth | 3' 0" | 3' 0" | 3' 2" | 3' 11" | 4' 6" | 4' 9" | 5' 0" | 5' 4" |
| Loading Height | 3' 6" | 3' 6" | 3' 8" | 4' 5" | 5' 0" | 5' 3" | 5' 6" | 6' 9" |
| Outlet Size | 9x9" | 9x9" | 9x9" | 14x16" | 14x16" | 14x16" | 14x20" | 14x20" |
| Overall Length | 4' 7" | 5' 10" | 7' 9" | 9' 6" | 10' 6" | 12' 4" | 13' 6" | 16' 1" |
| Overall Width | 4' 8" | 4' 8" | 4' 11" | 5' 7" | 6' 4" | 7' 0" | 7' 6" | 8' 11" |
| Overall Height | 4' 11" | 4' 11" | 5' 2" | 6' 3" | 6' 11" | 7' 2" | 7' 4" | 8' 9" |
| Weight In Pounds | 1,600 | 1,900 | 3,100 | 4,750 | 6,300 | 7,500 | 10,300 | 13,000 |

For ingredients which weigh up to 35 pounds per cubic foot, our Standard Duty Mixers are required, 35 to 50 pounds per cubic foot require our Heavy Duty Mixer while ingredients that weigh 50 to 70 pounds per cubic foot require our Super Duty Batch Mixer. Material weighing 100 to 150 pounds per cubic foot requires our Maximum Duty Mixer.

Questions, Comments about any of our products or this page please let us know! Info@HCDavis.com

H. C. Davis Sons Manufacturing Co., Inc.

P.O. Box 395 Bonner Springs, KS 66012

Phone: 913-422-3000 Fax: 913-422-7220 E-Mail: info@hcdavis.com